Contents lists available at ScienceDirect

## **Composites Part B**

journal homepage: www.elsevier.com/locate/compositesb

## Radiation stability and thermal behaviour of modified UF resin using biorenewable raw material-furfuryl alcohol

Suzana Samaržija-Jovanović<sup>a,\*</sup>, Vojislav Jovanović<sup>a</sup>, Branka Petković<sup>a</sup>, Slaviša Jovanović<sup>b,c</sup>, Gordana Marković<sup>d</sup>, Slavica Porobić<sup>e</sup>, Milena Marinović-Cincović<sup>e,\*</sup>

<sup>a</sup> Faculty of Natural Science and Mathematics, University of Priština, Lole Ribara 29, 38220 Kosovska Mitrovica, Serbia

<sup>b</sup> Faculty of Technology, University of Novi Sad, Bulevar cara Lazara 1, 21000 Novi Sad, Serbia

Trelleborg Wheel System, Business Unit Agricultural & Forestry Tires, Industrijska bb, 22400 Ruma, Serbia

<sup>d</sup> A.D. Tigar, Nikole Pašića 213, 18300 Pirot, Serbia

<sup>e</sup> Institute of Nuclear Science Vinča, University of Belgrade, Mike Petrovića Alasa 12-14, 11000 Belgrade, Serbia

ARTICLE INFO

Keywords: Resins Thermal properties Thermal analysis Cure Radiation stability

## ABSTRACT

The thermal stability of organic-inorganic nano-composites prepared by a two-stage polymerization of ureaformaldehyde resin (UF) with furfuryl alcohol (FA) and TiO<sub>2</sub> before and after irradiation has been researched. The two resins of urea-formaldehyde-TiO<sub>2</sub> composites, named: UF/TiO<sub>2</sub> and UF/TiO<sub>2</sub>/FA, were synthesized. The thermal stability of obtained materials was studied by non-isothermal thermo-gravimetric analysis (TG), differential thermal gravimetry (DTG) and differential thermal analysis (DTA). UF hybrid composites have been irradiated (50 kGy) and after that their radiation stability was evaluated on the basis of thermal behavior. The free formaldehyde (HCOH) percentage in all prepared samples was determined. The minimum percentage values of free formaldehyde (0.04% and 0.03%) for UF/TiO2 and UF/TiO2/FA, respectively, after irradiation dose of 50 kGy are detected. The shift of temperature values for selected mass losses ( $T_{10}$ %) to a high temperature indicates the increase in thermal stability of samples based on UF resin modified with FA.

\* Corresponding author.

\*\* Corresponding author.

E-mail addresses: vojani@sbb.rs, suzana.samarzija@pr.ac.rs (S. Samaržija-Jovanović), milena@vinca.rs (M. Marinović-Cincović).

https://doi.org/10.1016/j.compositesb.2018.12.024

Received 8 August 2018; Received in revised form 18 November 2018; Accepted 8 December 2018 Available online 10 December 2018

1359-8368/ © 2018 Elsevier Ltd. All rights reserved.





